

Declaration of Performance 305/2011(574/2014)

DOP No. RGHSPL/DOP/EN10210/S2351RH

Sr. No	Performance Particulars	De	escription	
1	Unique of product type	EN 10210-1:2006 Hot rolle	EN 10210-1:2006 Hot rolled Seamless of S235JRH.	
2	Intended use of construction products:	Metal structures or in composite metal and concrete structures		
3	Manufacturer:	RASHMI GREEN HYDROGEN STEEL PRIVATE LIMITED (Seamless Division) Vill & Mouja-Changual, Jethia, Khatranga, Gopinathpur, Goyalara, P.O - Changual, P.S - Kharagpur (Local), Dist- Paschim Medinipur, West Bengal, 721301, India		
4	Contact address of authorized representative:	Murlidhar Gawande. RASHMI GREEN HYDROGEN STEEL PRIVATE LIMITED (Seamless Division) Vill & Mouja-Changual, Jethia, Khatranga, Gopinathpur, Goyalara, P.O - Changual, P.S - Kharagpur (Local), Dist- Paschim Medinipur, West Bengal, 721301, India		
5	Assessment system and verification for constancy of performance	2+		
6(a)	Harmonized Standard	EN 10210-1:2006	€ **	
	Notified Body	construction product regular performed initial inspection	& Co. KG, notified body for ation (CPR), Reg No. 0045 of manufacturing plant under ificate of conformity of the factor	
6(b)	European Assessment	NA		
7	Declared Performance			
	Essential Characteristics	Performance	Harmonized Technical Specification	
	Tolerance on dimensions and shape	EN 10210-2:2019	EN 10210-2:2019	
	Mechanical Properties			
	Tensile Strength(MPa)	Hot Rolled Strip= 360 - 510 Mpa	EN 10210-1:2006	
	Yield Strength(MPa)	Hot Rolled Strip = 235 Mpa min	EN 10210-1:2006	
	Elongation (%)	Minimum 26 % (EN 10210-1 Table A.3)	EN 10210-1:2006	
	Impact Strength(20deg C)	27 (Joules) – Longitudinal	EN 10210-1:2006	
	Weld ability (cover by	Satisfactory	EN 10210-1:2006	
	chamical composition)			
	chemical composition)			
	Durability (cover by	NPD		
		NPD < 100PPM		

Signature:

Murlidhar Gawande. Dy. Manager(QA/QC)

Place: Kharagpur (India). Date: 15/04/2024.